




































# COMMUTATEUR ELECTRIQUE ROTATIF

## DATASHEET & CATALOG



## JS PRODUCT SPECIFICATIONS JS

COMMUTATEUR Rotatif 2P,3P	Contact position		Position	Description	Type code	Overall dimensions
			 keyout	 Locked	 spring reset	
	N/O			2 positions		
	N/O	N/C				
	N/O					
	N/O	N/C				
	2N/O			3 positions		
	2N/O					
	2N/O					
	N/O			2 positions		
	N/O	N/C				
	N/O					
	N/O	N/C				
	2N/O			3 positions		
	2N/O					
	2N/O					
	N/O			2 positions		
	N/O	N/C				
	N/O					
	N/O	N/C				
	N/O			Ronis n° 455 Key switch n° 455		
	N/O	N/C				
	2N/O					
	2N/O					
	2N/O					
	2N/O					




## JS PRODUCT SPECIFICATIONS JS

TYPE	JSLW28-20	JSLW28-25	JSLW28-32	JSLW28-63	JSLW28-125	JSLW28-160
RATED INSULATION VOLTAGE UI(V)	690	690	690	690	690	690
CONVENTIONAL HEATING CURRENT ITH(A)	20	25	32	63	125	160
RATED WORKING VOLTAGE UE(V)	120 240 440	120 240 440	120 240 440	240 440	240 440	220 440
RATED WORKING CURRENT IE (A)	AC-21A AC-22A	360 360				
	AC-23A	15 15	22 22	22 30 30	57 57	90 90 135 135
	AC-2	15 15	22 22	223030	57 57	90 90 135 135
	AC-3	11 11	15 15	152222	36 36	75 75 95 95
	AC-4	3.5 3.5	6.5 6.5	6.511 11	15 15	30 30 95 95
	AC-15	5 4	8 5	5 14 6		
	AC-13	5	9 1.5	2511		
RATED CONTROL POWER(KW)	AC-23A	3.7/2.5 7.5/37	5.5/31/5.5	7.5/4 15/7.5	15/10 30/18.5	30/15 45/22 37/22 75/3
	AC-2	4 7.5	5.5 11	7.5 15	18.5 30	30 45 37 55
	AC-3	3/2.2 5.5/3	4/3 7.5/3.7	5.5/4 11/5.5	11/6 18.5/11	15/7.5 30/13 22/11 37/18
	AC-4	0.55/0.75 1.5/1.5	1.5/1.1 3/2.2	3.7/1.5 5.5/3	5.5/2.4 7.5/4	12/5.5 10/4 15/7
MECHANICAL LIFE	60 x 10 <sup>4</sup>					
ELECTRICAL LIFE	AC-1520x DC-136 x IOA4					


## JS PRODUCT DIMENSIONS JS

TYPE	PANEL SHAPE	EXTERNAL DIMENSION(MM)				MOUNTING DIMENSION(MM)			
		A	B	C	L	a	b	diameter 1	diameter 2
JSW28-20	M1 square	48	48	43	22+9.6n	36	36	8.5	4.5
	M1 rectangular	48	60	43	22+9.6n	36	36	8.5	4.5
	M2 square	64	64	43	25+9.6n	48	48	10	4.5
	M2 rectangular	64	80	43	25+9.6n	48	48	10	4.5
JSW28-25	M1 square	48	48	45.2	23+12.8n	36	36	8.5	4.5
	M1 rectangular	48	60	45.2	23+12.8n	36	36	8.5	4.5
	M2 square	64	64	45.2	26.5 +12.8n	48	48	10	4.5
	M2 rectangular	64	80	45.2	26.5 +12.8n	48	48	10	4.5
JSW28-32	M2 square	64	64	58	29.2 +21.5n	48	48	10	4.5
	M2 rectangular	64	80	58	29.2 +21.5n	48	48	10	4.5
JSW28-63	M2 square	64	64	66	29.2 +21.5n	48	48	10	4.5
	M2 rectangular	64	80	66	29.2 +21.5n	48	48	10	4.5
	M3 square	64	88	66	29.2 +21.5n	68	68	10	4.5
	M3 rectangular	88	107	66	29.2 +21.5n	68	68	10	4.5
JSW28-125	M3 square	88	88	84	35 +26.5n	68	68	13	6
	M3 rectangular	88	107	84	35 +26.5n	68	68	13	6


SMALL PANEL MOUNTING DIMENSION DIAGRAM



BIG PANEL MOUNTING DIMENSION DIAGRAM



OVERSIZE PANEL MOUNTING DIMENSION DIAGRAM



## JS PRODUCT DISPLAY JS

	1	3	5	7	9	11
0						
1	X		X		X	
0						
2		X		X		X

